

NEW BULLETIN

1. **MANDATORY:** Remove all radar receiver fuses prior to starting the System Reset procedure.
2. In the event you need to replace a Calibre component (radar receiver or Interior Network Module), do so now before moving to Step 3.
3. Start the vehicle. Then, turn CALIBRE system **OFF** by *pressing and releasing* the **HWY/CITY/OFF** button until the **OFF** mode LED illuminates and a voice confirmation states **"K40 OFF"** (see Figure 1). Allow mode LEDs to turn off.
4.
 - a. Reactivate Remote Control by *pressing and releasing* **MUTE** button (see Figure 2).
 - b. While mode LEDs are illuminated, *press and hold* the **MUTE** button for approximately five seconds until the **MUTE** mode LED begins flashing *and then release* the button (see Figure 3).
 - c. While **MUTE** mode light is still flashing, *press and release* the **MUTE** button once (see Figure 4).
5. Upon successful completion of the above steps, CALIBRE will provide a voice confirmation that states **"K40 RESET"** and the **HWY**, **VOICE**, and **HIGH** LEDs illuminate. Allow mode LEDs to turn off.
6. Turn vehicle **OFF** and reinsert all radar receiver fuses. Then start the vehicle. CALIBRE will provide voice confirmation of **"CONNECTING..."**.
7. CALIBRE will now begin the process of establishing its wireless connection to all system components. This process can take up to 10 minutes.
8. When a connection is established, a voice confirmation will state **"FRONT CONNECTED"** and if equipped with a rear radar receiver, a voice confirmation will state **"REAR CONNECTED."** This connection confirmation sequence may vary in order and in timing.
9. The system mode settings are now as they were originally set at the factory with **HWY**, **VOICE**, and **HIGH** modes selected.

