

RD950 QUICK REFERENCE GUIDE

Menu / Customizable Settings

- **Press and release MENU button** to scroll through the preferences until you reach the option to be changed.
- To change setting, **press and release MUTE button**. Both the display and voice will announce the change.
- **Press and release MENU button** to continue scrolling to another preference.

Menu Options <i>(in order displayed)</i>		Default Setting	Description
1	Voice Type	Female	Choose male or female voice for audio alerts.
2	Audible Voice	On	For all initial audio alerts: "Voice On" uses voice; "Voice Off" uses tones only.
3	Wake-Up	Wake-Up Long	"Wake-Up Long" is a standard 5-second sequence. "Wake-Up Short" uses an abbreviated sequence.
4	Traffic Sensor Filter	Off	Enables filtration of K-Band radar signals from traffic flow sensors.
5	Automute	Off	Automatically reduces volume by 50% after 5 seconds.
6	X-Band	On	Enables the detection of X-Band radar.
7	K-Band	On	Enables the detection of K-Band radar.
8	Ka-Band	On	Enables the detection of Ka-Band radar.
9	Laser	On	Enables the detection of laser.
10	Factory Reset	RESET	Original factory default for all settings.

Radar Alert Signals

Radar source strength:	weak	medium	strong
Display reading:	1 2 3	4 5 6	7 8 9
Audio alert beeps:	slowly		rapidly

RD950 QUICK REFERENCE GUIDE

Frequently Used Features & Functions

Mute Audio Before or During Alert *(Owner's Manual pg.11)*

30-second Mute	Press and release MUTE button.
5-minute Mute	Press and hold MUTE button for 3 seconds.

DIM *(Owner's Manual pg.10)*

- **Press and release DIM button** to adjust display brightness to accommodate various driving environments. Your setting will automatically be saved with the exception of "Off." The "Off" setting will revert to "Auto" upon RD950 wake-up.

The 5 options include:

1. **"Day"** *(Bright)*
2. **"Dusk"** *(Medium / factory default)*
3. **"Night"** *(Dim)*
4. **"Auto"** *(Display adjusts automatically from 5 seconds in "Day," 5 seconds in "Dusk," and the duration of the alert in "Night")*
5. **"Off"** *(No display, still receive full audio alerts)*

FILTER *(Owner's Manual pg.10)*

(i.e. signal sensitivity)

The **FILTER button** offers three levels of sensitivity: Highway (full sensitivity), City (X-Band 50%), and Filter (X-Band Off, K and Ka-Band 50%). To change the level at any time, **press and release FILTER button.**



Learn more at K40.com

© K40 Electronics

Questions? Call **800.323.5608**

44818-1 4/16